



BA-AL ALUMINUM INSULATED ACCESS DOOR

The BA-AL Aluminum Insulated Access Door is a light weight insulated aluminum access door. It is ideal for exterior applications, and also those specific interior applications where corrosion or moisture is a concern. The aluminum panel is insulated with 1" Silverboard Ridge Foam Insulation. Access to large openings in walls and ceilings is made easy. The non-extruded door frame has the same visual aesthetic design as the UAD door. Weather resistant neoprene gasketing is installed on 4 sides.

FEATURES

Door and Trim	.063 Aluminum, trim 1 1/2" wide
Return Frame	.063 Aluminum, depth of 2"
Hinge	Continuous rod hinge
Latches	Flush aluminum steel cam
Insulation	1" AMVIC Silverboard Ridge Foam Insulation with a R5 Value
Gasket	Neoprene gasket included on 4 sides
Finish	Mill finish
Options (at extra cost)	Key medium barrel cylinder lock with key (code 151)


Model No.	A x B Door Size	Cam Latch	Shipping Weight (lbs) Steel/Stainless
BA-AL 8x8	8" x 8"	1	3.5
BA-AL 12x12	12" x 12"	3	6
BA-AL 16x16	16" x 16"	3	9
BA-AL 18x18	18" x 18"	3	15
BA-AL 24x24	24" x 24"	4	24
BA-AL 24x36	24" x 36"	5	45

Rough wall opening = door size + 1/4"




BA-AL

DIMENSIONS



Elevation



Section Detail