

BA-ED-2002

UNIVERSAL FLUSH

Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface
- Economical and attractive access door for walls & ceilings

Product Features

- Formed door panel
- Concealed hinge

BA-ED-2002 Access Door Specifications:

Material: 18 gauge steel door and frame

Door: Flush to frame with reinforced edges

Door Frame: 1" wide outside flange with 1 7/16" deep mounting Frame: Knock over mounting tabs provided on 6x6, 8x8, 10x10 and 12x12

Hinge: Concealed Hinge Pin

Latch: Stainless steel slot screwdriver operated cam latch

Finish: 5 Stage iron phosphate preparation with prime coat of White alkylid baking enamel

BA-ED-2002 STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
6 X 6	152 X 152	1	1.7	.8
8 X 8	203 X 203	1	2.5	1.1
10 X 10	254 X 254	1	3.5	1.6
12 X 12	305 X 305	1	4.6	2.1
14 X 14	355 X 355	1	5.8	2.6
16 X 16	406 X 406	1	7.2	3.3
18 x 18	457 x 457	1	8.8	4.0
20 x 20	508 x 508	1	10.4	4.7
24 x 24	610 x 610	1	14.2	6.4
24 x 36	610 x 915	2	17.0	7.7

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

