



SPECIFICATIONS

1. THERMALLY BROKEN CURB W/INTEGRAL CAPFLASHING 11 GA. ALUMINUM (CORNERS FULLY WELDED)
2. EXTRUDED ALUMINUM COVER FRAME
3. DOUBLE DOME W/ SEALANT ALL AROUND (CLEAR POLYCARBONATE OVER CLEAR POLYCARBONATE)
4. 3" [75mm] POLYISOCYANURATE CURB INSULATION
5. CONDENSATE CHANNEL W/ DRAINAGE TO EXTERIOR
6. EPDM GASKET (ALL AROUND COVER)
7. PINTLE HINGE - STAINLESS STEEL TYPE 316
8. Bilclip® FLASHING SYSTEM
9. SLAM LATCH WITH INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
10. LOCK STRIKE AND PADLOCK HASP
11. LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
12. AUTOMATIC HOLD OPEN ARM W/ RED VINYL GRIP AND COVER RELEASE
13. ARM GUIDE BRACKET

SHOP FINISH

ALUMINIUM: MILL FINISH
 HARDWARE: CORROSION RESISTANT (UNLESS OTHERWISE SPECIFIED)

NOTES:

1. THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.
2. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: www.bilco.com

CUSTOMER

P.O. NO.

JOB

SALES REP.



www.BestAccessDoors.ca
 Fax: 1-888-828-6021
 Phone: 1-800-483-0823
 Email: info@BestAccessDoors.ca

**SINGLE LEAF ROOF ACCESS HATCH
 TYPE GS-50TB**

QTY	TYPE	SIZE
		WIDTH x LENGTH
<input type="checkbox"/>	GS-50TB	3'-0" x 2'-6" 915mm x 760mm HINGE SIDE