



Quality Access Doors - FAST !



DUCT DOORS for Sheet Metal Duct BA-HD-5070

Application

- Assures a tight seal without obstruction in the air system

Product Features

- Insulated door panel, along with the gasketing between the door and frame
- 5/8" notched knock over tabs on the inside of the frame provide for easy installation
- These doors are designed for use in LOW to medium pressure up to 3" static W.G.

Options:

- ALUMINUM
- STAINLESS STEEL
- CYLINDER LOCK & KEY
- HASP + STAPLE
- L HANDLE

BA-HD-5070 Duct Access Door Specifications:

Door: 24 gauge galvanized steel, double panel

Frame: 24 gauge galvanized steel with 5/8" notched knock over tabs

Hinge: Continuous aluminum piano hinge

Insulation: Door panel filled with 2" fibreglass insulation (7.7 R factor), compressed into 1".

Gasketing: 1/8" thick by 1/2" wide closed cell neoprene gasketing between door and frame and also between frame and duct

Latch: Self tightening, hand operated cam latch



STANDARD SIZES (Special sizes available upon request)

| NOMINAL DOOR SIZE W X H | | Opening | WEIGHT PER DOOR | |
|-------------------------|-----------|-----------------|-----------------|-----|
| inches | mm | | lbs. | kg. |
| 6 X 6 | 150 X 150 | 4-3/4 X 4-3/4 | 1.25 | 0.6 |
| 8 X 8 | 200 X 200 | 6-3/4 X 6-3/4 | 1.75 | 0.8 |
| 10 X 10 | 250 X 250 | 8-3/4 X 8-3/4 | 2.75 | 1.3 |
| 12 X 12 | 300 X 300 | 10-3/4 X 10-3/4 | 3.75 | 1.7 |
| 14 X 14 | 350 X 350 | 12-3/4 X 12-3/4 | 4.75 | 2.2 |
| 16 X 16 | 400 X 400 | 14-3/4 X 14-3/4 | 5.25 | 2.4 |
| 18 X 18 | 450 X 450 | 16-3/4 X 16-3/4 | 6.75 | 3.1 |
| 20 X 20 | 500 X 500 | 18-3/4 X 18-3/4 | 9 | 4.1 |
| 24 X 24 | 610 X 610 | 22-3/4 X 22-3/4 | 12 | 5.5 |

Duct opening is nominal door size -1 1/4" (31 mm)
For detailed specifications see submittal sheet

