



228 Park Ave S # 76520 New York NY  
 10003-1502 United States  
 www.BestAccessDoors.com  
 sales@bestaccessdoors.com  
 Tel.: 1-800-483-0823  
 Fax: 1-888-828-6021

# FIRE RESISTIVE ACCESS DOOR

## BA-KATR-LL

### Lead Lined Access Door

**DATE:**



**CONSTRUCTION:**

1. Frame shall be 16 gage steel and doors all be 18 gage steel.
2. Door shall be recessed 1 1/2" to accommodate double thickness of wall board.
3. Hinge shall be exposed, continuous piano hinge.
4. Locks shall be flush and screwdriver operated with 1 1/2" stainless steel cam and lock studs, or shall be key operated cylinder lock with automatic dust shutter. Furnished with plastic grommet for studs only to protect hole made in wall board.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked grey enamel.
6. Sheet metal meets National Council of Radiation Protection Report #49.
7. Varying thicknesses of lead available. Custom door sizes also available.

PROJECT DATA					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					

PROJECT SCHEDULE					
Qty.	H	W	No. of Latches	Finish	Remarks

**STANDARD SIZES**

DOOR SIZE H X W (IN.)	WALL/CEILING OPENING (IN.)	NUMBER OF LATCHES	SHIP WT. (LBS.)
12 x 12	10 1/2 x 10 1/2	1	6.7
18 x 18	16 1/2 x 16 1/2	2	11.6
24 x 24	22 1/2 x 22 1/2	2	18.1
30 x 22	28 1/2 x 20 1/2	2	19.5

