



**SPECIFICATIONS**

1. heavy duty forced brass hinges with stainless steel pins
2. Guide arm (if req'd)
3. 1-1/2" drain coupling
4. Standard slam lock
5. Cam assembly
6. automatic hold open arm w/ red vinyl grip
7. 1/4" aluminum diamond pattern plate cover
8. 1/4" aluminum channel frame with extruded anchor flange
9. Stainless steel lock strike
10. Torsion rods (stainless steel)

SHOP FINISH:  
 ALUMINUM: MILL FINISH  
 HARDWARE: ZINC PLATED & CHROMATE SEALED  
 (unless otherwise specified)

REINFORCED FOR 300 Lbs. PER Sq. Ft.  
 (1464 kg. PER Sq. METER) LIVE LOAD

**INSTALLER NOTES:**

- A. Use caution. Cover is spring loaded. Do not remove safety shipping bolt until unit is to be installed and in normal horizontal operating position.
- B. Be sure unit is set on slight pitch toward drain corner.
- C. Before anchoring in place open and close door. Check to see that the door in the closed position rests on the frame all around. If not, shim under the frame at the proper corner.
- D. Do not reduce 1 1/2" drain pipe to dry well or disposal system.

*Customer:*

*P.O. N°*

*Job:*

*Sales Rep:*



www.BestAccessDoors.ca  
 Fax: 1-888-828-6021  
 Phone: 1-800-483-0823  
 Email: info@BestAccessDoors.ca

**SINGLE LEAF ACCESS DOOR  
 TYPE PCM - INTERIOR/EXTERIOR  
 SIZE**

QTY	TYPE	WIDTH x LENGTH
<input type="checkbox"/>	PCM-1	2'-0" x 2'-0" [610mm] x [610mm]
<input type="checkbox"/>	PCM-2	2'-6" x 2'-6" [762mm] x [762mm]
<input type="checkbox"/>	PCM-3	3'-0" x 2'-6" [914mm] x [762mm]
<input type="checkbox"/>	PCM-4	3'-0" x 3'-0" [914mm] x [914mm]
<input type="checkbox"/>	PCM-5	3'-6" x 3'-6" [1065mm] x [1065mm]