



## SPECIFICATIONS

1. THERMALLY BROKEN CURB W/INTEGRAL CAPFLASHING 11 GA. ALUMINUM (CORNERS FULLY WELDED)
2. THERMALLY BROKEN COVER – 11 GA. ALUMINIUM
3. COVER LINER – 18 GA. ALUMINIUM
4. 3" [75mm] POLYISOCYANURATE CURB INSULATION
5. 3" [75mm] POLYISOCYANURATE COVER INSULATION
6. EPDM GASKET (ALL AROUND COVER)
7. PINTLE HINGE – STAINLESS STEEL TYPE 316
8. Bilclip® FLASHING SYSTEM
9. SLAM LATCH WITH INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
10. LOCK STRIKE AND PADLOCK HASP
11. LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
12. AUTOMATIC HOLD OPEN ARM W/ RED VINYL GRIP AND COVER RELEASE
13. ARM GUIDE BRACKET

## SHOP FINISH

ALUMINIUM: MILL FINISH  
HARDWARE: CORROSION RESISTANT (UNLESS OTHERWISE SPECIFIED)

## NOTES:

1. THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.
2. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: [www.bilco.com](http://www.bilco.com)

## CUSTOMER

## P.O. NO.

## JOB

## SALES REP.



[www.BestAccessDoors.ca](http://www.BestAccessDoors.ca)  
Fax: 1-888-828-6021  
Phone: 1-800-483-0823  
Email: [info@BestAccessDoors.ca](mailto:info@BestAccessDoors.ca)

## SINGLE LEAF ROOF ACCESS HATCH TYPE S-50TB

QTY	TYPE	SIZE
		WIDTH x LENGTH
<input type="checkbox"/>	S-50TB	3'-0" x 2'-6" 915mm x 760mm HINGE SIDE