



Quality Access Doors - FAST !



SPECIALTY DOORS

Surface Mounted

BA-SF-2000

Application

- An innovative surface mounted access door for all types of walls and ceilings

Product Features

- An exposed continuous piano hinge allows the door panel to open to 175 degrees
- There is no frame to extend into the wall or ceiling
- Perfect for access to odd size openings

BA-SF-2000 Access Door Specifications:

Door / Door Frame: Steel: 16 gage, flush to frame with rounded safety corners and a one piece outer flange
Frame is one piece outer flange

Hinge: Exposed continuous piano hinge

Standard Latch: Stainless steel screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock & key, allen head cam latch, spanner head cam latch

Finish: 5 stage iron phosphate preparation with White alkyd baked-on enamel



STANDARD SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
8 X 8	203 X 203	1	2	0.9
12 X 12	305 X 305	1	4	1.8
16 X 16	406 X 406	2	6	2.7
24 X 24	610 X 610	4	14	6.4

Wall & Ceiling opening is W - 1/4" (7 mm)
For detailed specifications see submittal sheet

