

Quality Access Doors- FAST

DESCRIPTION

The access panel consists of aluminium profiles, a Hardie Board insert and a round cylinder lock with key. Both, an outer and an inner frame of the access panel consist of four single frames, which are firmly connected due to a special welding process.

The access panel is equipped with a safety-system against accidental opening. In order to avoid accidents, this safety-system has to be secured after each opening. A joint gap of ¼" (3 mm) is visible between outer frame and door leaf, which is equipped with an innovative brush joint (air-tight and dustresistant) and, in addition, with a special joint (water resistant). Access panels for facades in the outer area are applicable for direct mounting into solid walls (without external wall insulation system) or for installation into a wall insulation system (foamsealed).

ADVANTAGES

· Economical solution

- Delivery at short notice on request
- Easy and quick assembly
- Solid aluminium frame
- Sophisticated solution
- Flush installation in facades

For a complete list of options visit www.BestAccessDoors.ca



To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET

SKU: BAC-MPLV **DRYWALL ACCESS PANEL** FOR EXTERIOR FACADE

DIMENSIONS AND APPEARANCE

STANDARD SIZES:

SYSTEM MPL	DIMENSIONS				
CODE	A inch I mm	B inch I mm			
MPL203203	8" 203	8" 203			
MPL305305	12" 305	12" I 305			
MPL406406	16" I 406	16" I 406			
MPL508508	20" 508	20" 508			
MPL610610	24" 610	24" 610			

OPTIONS:

- -Screwdriver operated cam latch SD
- Screwdriver operated four-square cam latch FS -
- Ζ Round Cylinder Lock with Key
- Μ Mortise Cylinder Lock Preparation
- Н Hex Head Cam Latch
- Ρ Pinned Hex Head Cam Latch

Ver. 2: For direct Ver. 1: For direct mounting into solid walls mounting into solid walls MPL MPL



PROJECT DATA

PROJECT NAME :	QTY	w	Н	OPTIONS	
ARCHITECT :					
DEALER :					
CONTRACTOR :					
LOCATION :	SPECIAL INSTRUCTIONS :				
DATE :					
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)				





385 WILSON STREET EAST, **SUITE 302** ANCASTER, ON, L9G 2C1 CANADA

WEBSITE: www.BestAccessDoors.ca



Version: 1 14" (6 •35 mm) Hardie Board inlay Α with J B

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

Customized sizes can be produced in every dimension upon request.

Ver. 3: For installation into a wall insulation system MPLV

Ver. 4: For installation into a wall insulation system MPLV



Custom Sizes Available - Fast!



