

STANDARD OPTIONS

MATERIAL:

16 gauge cold rolled steel frame & 14 gauge galvanneal steel door

HINGE:

Continuous piano hinge

INSULATION:

Mineral wool

LOCK / LATCH:

Self latching tool-key operated slam latch and/or ring operated slam latch, both included

INSIDE PANEL RELEASE:

Standard on all doors over 12" x 12"

AUTOMATIC PANEL CLOSER:

Standard on all doors

FINISH:

High quality white powder coat primer

PACKAGING:

Individually wrapped, 1 per box

OPTIONS AVAILABLE

LOCK / LATCH:

- Mortise deadbolt lock
- Hex head slam latch
- · Handle operated cam latch
- Mortise preparation for cylinder (cylinder optional)

MATERIAL:

Stainless steel 304 #4 (brushed finish) **MASONRY ANCHOR:**

Available on all sizes

Fire Rating information on Page 2

For a complete list of options visit www.BestAccessDoors.ca





To view Pricing and Additional Product Info.

LEED READY: THIS PRODUCT CONTRIBUTES TO LEED® CREDITS



SUBMITTAL/TECHNICAL DATA SHEET

SKU: BAC-PFI-HS


FIRE RATED INSULATED ACCESS DOOR

FOR ALL SURFACE TYPES



INSTALLATION

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<




[1 HOUR CEILING APPLICATION] Authorities Having Jurisdiction (AHJ) should be consulted in all cases as to the particular Steel or requirements covering the installation and use of fire rated access doors

DIMENSIONS AND APPEARANCE

STANDARD SIZES:

DOOR SIZE W x H INCHES (MM)		NUMBER OF LOCKS	WEIGHT LBS KG	
8 x 8	(203 x 203)	1	7	3.2
10 x 10	(254 x 254)	1	8	3.6
12 x 12	(304 x 304)	1	10	4.5
14 x 14	(355 x 355)	1	12	5.4
16 x 16	(406 x 406)	1	14	6.4
18 x 18	(457 x 457)	1	17	7.7
22 x 22	(558 x 558)	1	20	9.1
22 x 30	(558 x 762)	1	30	13.6
22 x 36	(558 x 914)	2	34	15.5
24 x 24	(609 x 609)	1	28	12.7
24 x 36	(609 x 914)	2	36	16.4
* 24 x 48	(609 x 1219)	2	48	21.8
* 30 x 30	(762 x 762)	1	40	18.1
* 32 x 32	(812 x 812)	2	43	19.5
* 36 x 36	(914 x 914)	2	50	22.7
* 48 x 48	(1219 x 1219)	2	83	37.7



ROUGH WALL OPENING IS DOOR SIZE + 1/4" OR + 6MM

^{*} Not available for ceiling rating (maximum 24"x36")

■ PROJECT DATA			Custom Sizes Available - Fast!			
PROJECT NAME:	QTY	W	Н	OPTIONS		
ARCHITECT:						
DEALER:						
CONTRACTOR:						
LOCATION:	SPECIAL	SPECIAL INSTRUCTIONS:				
DATE:						
TAGGING INSTRUCTIONS:	SUBMITTAL APPROVAL : (signature or stamp)					





SUITE 302

CANADA



BAC-PFI-HS

FIRE RATED INSULATED ACCESS DOOR FOR ALL SURFACE TYPES

FIRE RATING

FOR INSTALLATION IN VERTICAL WALL ASSEMBLIES:

CERTIFIED TO STANDARDS: UBC 7-2 (1997), UL 10B (1997), UL 10B (2009), NFPA 252 (2003), NFPA 252 (2008), NFPA 252 (2012), CAN/ULC S104 (R1985), CAN/ULC S104 (2010). RATING ACHIEVED: 3 hours, neutral/negative pressure. MAXIMUM SIZE: 48" wide x 48" high (1219 mm x 1219 mm). Maximum area of 2304 in²

Tolerance on height and width limitation is \pm 3" (76 mm) as long as the area does not exceed 2304 in²

TEMPERATURE RISE: 250°F (121°C) after 30 min. 450°F (232°C) after 60 min.

FOR INSTALLATION IN HORIZONTAL CEILING ASSEMBLIES:

CERTIFIED TO STANDARDS: ASTM E119 (2012), CAN/ULC S101 (2007).


RATING ACHIEVED: 3 hours in non-combustible construction. 1 hour in combustible construction.

MAXIMUM SIZE: $24" \times 36"$ (hinges & latch on 36" long sides) (610 mm x 914 mm).


Tolerances on dimension limitations are \pm 3" (76 mm) as long as the area does not exceed 864 in²

TEMPERATURE RISE: Not applicable.

■ INSTALLATION: WALLS AND CEILINGS



[1 HOUR CEILING APPLICATION]



Authorities Having Jurisdiction (AHJ) should be consulted in all cases as to the particular requirements covering the installation and use of fire rated access doors.



