



Quality Access Doors- **FAST!**

## APPLICATION

Folding section attic ladder LMP allows access to the attic space, even in very high rooms, while maintaining maximum comfort and safety of use. Supported room height range from 9'10" to 12'.

## SPECIFICATIONS

### HATCH:

Insulated, sandwich type,  
Thickness: 1 3/8".  
Thermal insulation thickness: 1 1/8".

### FRAME:

Pinewood.  
Height: 7 1/8"  
Seal: 1x

### LADDER:

Metal  
Ladder width: 15"  
Stringer height: 3 1/8"  
Distance between steps: 9 1/2".

### STEPS:

Metal, equipped with anti-slip profile.  
Step width: 3 1/8"  
Length: 13 3/8"

### STANDARD ACCESSORIES:

Plastic ends  
Handrail with unloading mechanism.  
Lightweight aluminum telescopic rod to open the hatch.

# SUBMITTAL/TECHNICAL DATA SHEET

SKU: **BAC-LMP**

## METAL ATTIC LADDERS



## DIMENSIONS AND APPEARANCE

[>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

### DIMENSIONS:

Rough Opening	Room Height
22.5" x 56.5"	9'10" - 12'
25" x 56.5"	
30" x 56.5"	

### TECHNICAL PARAMETERS:

Maximum Loading
375 lbs
Heat Transfer Coefficient
R-value: 5.2

### COMPATIBLE ACCESSORIES:

Ladder Balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.
Installation brackets LXX	Maximum ceiling 15 3/8"
Wooden trim LXL-W	The trims are available in size 30"x56,5" for smaller sizes have to be cut.
PCV trim LXL-PVC	The trims are available in size 30"x56,5" for smaller sizes have to be cut.
Box extension LXN	The standard box height is 4". While ordering the LXN please provide ladder type and size.
Upper hatch LXW	The height of the upper hatch box is 7 3/4".

### ASSEMBLY INFORMATION


The LMP attic ladder is delivered to the customer fully assembled, it requires only screwing side elements of the supports which for transport purposes are unscrewed. The length of the last segment should be cut on-site to suit to existing ceiling height. Installation of the product must be carried out in accordance with the included fitting instructions.

For more details see the second page

## PROJECT DATA

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

For a complete list of options visit  
[www.BestAccessDoors.ca](http://www.BestAccessDoors.ca)

Scan  or  Click



To view Pricing and  
Additional Product Info.

TELEPHONE:  
1-800-483-0823  
FAX:  
1-888-828-6021



385 WILSON STREET EAST,  
SUITE 302  
ANCASTER, ON, L9G 2C1  
CANADA



WEBSITE:  
[www.BestAccessDoors.ca](http://www.BestAccessDoors.ca)  
E-MAIL:  
[info@bestaccessdoors.ca](mailto:info@bestaccessdoors.ca)

# BAC-LMP

# METAL ATTIC LADDERS

SIZE:				
LWS		22 ½ x 56 ½	25 x 56 ½	30 x 56 ½
Manufacturer's part number		869331	869332	869333
Ceiling height	H	9'10" - 12'		
Rough opening	AxB	22 ½" x 56 ½"	25" x 56 ½"	30" x 56 ½"
Outside frame dimensions		22" x 56"	24 ½" x 56"	29 ½" x 56"
Internal frame dimensions		20 ½" x 54 ¾"	22 ⅞" x 54 ¾"	28" x 54 ¾"
Projection	R	77 ⅞"		
Landing space	C	57 ⅞"		
Folded ladder height	K	12 ⅝"		
Frame height		7 ⅞"		
Approx. Weight (lbs)		102	108	114

