



SUBMITTAL/TECHNICAL DATA SHEET

APPLICATION

LSF is an fire rated scissor attic ladder designed to provide safe and easy access to non-inhabited spaces. It eliminates a need for installing more expensive and space consuming staircases. Fire rated scissors metal model LSF for building codes require fire protections.

SPECIFICATIONS

HATCH:
Insulated, fire-resistant white hatch
Thickness: 2 1/8"
Thermal insulation thickness: 1 1/8"
Hatch equipped with a lock

FRAME:
Metal ladder box with metal trim and quick-installation brackets included
Height: 5 1/2"

LADDER: Metal scissor ladder.

STEPS:
Metal, equipped with anti-slip profile.
Tread width: 3 1/8"
Length: 11 1/8", 12 5/8",

STANDARD ACCESSORIES:
Control rod for opening the hatch

SKU: **BAC-LSF**

SCISSOR ATTIC LADDER



DIMENSIONS AND APPEARANCE

[>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

DIMENSIONS:

Rough Opening	Room Height
22 1/2" x 47"	8' 10 1/4" - 9' 10 1/8"
25" x 47"	

TECHNICAL PARAMETERS:

Maximum Loading
350 lbs
Fire-Rated
El ₂ = 60 min

COMPATIBLE ACCESSORIES:

Ladder Balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.
LSS additional step	To increase the length of the LSF ladder you can use an extra step: LSS-30 for size 22 1/2" x 47", LSS-32 for size 25 x 47.



ASSEMBLY INFORMATION

The LSF Attic Ladder is delivered to the customer fully assembled and does not require any pre-installation work. Installation of the product must be carried out in accordance with the included fitting instructions.

For more details see the second page

For a complete list of options visit
www.BestAccessDoors.ca

PROJECT DATA

Scan  or  Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

TELEPHONE:
1-800-483-0823
FAX:
1-888-828-6021





385 WILSON STREET EAST,
SUITE 302
ANCASTER, ON, L9G 2C1
CANADA



WEBSITE:
www.BestAccessDoors.ca
E-MAIL:
info@bestaccessdoors.ca

BAC-LSF

SCISSOR ATTIC LADDERS

SIZE:			
LSF		22x47	25 x 47
Ceiling height	H	8' 10 ³ / ₈ " - 9' 10 ¹ / ₈ "	
Rough opening	AxB	22 ¹ / ₂ "x47"	25"x47"
Outside frame dimensions		22"x46 ⁵ / ₈ "	24 ¹ / ₂ "x46 ⁵ / ₈ "
Outside frame dimensions including trim		24 ¹ / ₂ "x49"	27"x49"
Internal dimensions		20"x45 ¹ / ₄ "	22 ¹ / ₂ "x45 ¹ / ₄ "
Projection	R	67" - 71"	
Landing space	C	65" - 51 ¹ / ₄ "	
Folded ladder height	K	17 ³ / ₄ "	
Frame height		5 ¹ / ₂ "	
Step length	E	11 ⁷ / ₈ "	12 ⁵ / ₈ "
Step width		3 ¹ / ₈ "	
Possibility of adding additional steps		LSS-30	LSS-32

1 step removed		standard lenght of ladder (10steps)		1 additional step	
7'10 ¹ / ₂ "	8'10 ³ / ₈ "	8'10 ³ / ₈ "	9'10 ¹ / ₈ "	9'10 ¹ / ₈ "	10'6"
Ladder dimensions are equal to all sizes.					
65"	65"	67"	71"	72 ⁷ / ₈ "	82 ³ / ₄ "
39 ³ / ₈ "	55 ⁵ / ₈ "	65"	51 ¹ / ₄ "	47 ¹ / ₄ "	55 ⁵ / ₈ "

